

STATIC DISSIPATIVE LAMINATING SHEETS

Our ESD Laminating Sheet will work with any standard document laminating system which can be found at Office Max, Staples or at any office supply store.

INSTRUCTIONS: Take a Non-ESD document and place between 10^9 Ohms/sq sheets. Then laminate them together through a Heat Sealer. You now have a laminated static dissipative document holder that's safe for ESD sensitive areas.

STATIC DISSIPATIVE LAMINATING SHEETS AVAILABLE IN:

Part Number: SD-SHEETS *8 1/2 inches x 11 inches*
Part Number: SD-SHEETS-02 *12 1/4 inches x 17 inches*

CONSTRUCTION

Ingredients	Contents
PET	95%
EVA	5%

PHYSICAL PROPERTY

Description	Specifications
Thickness	80 micron
Grammage	95 gram/m ²
Elongation	MD 161 %
	TD 120

ELECTRICAL PROPERTY

Outer Surface Resistivity	< 10^9 Ohms/sq
Static Decay (1000V to 0V)	< 2 seconds
Part Numbers	SD-SHEETS, SD-SHEETS-02
Unit of Measure/Quantity	1 Pack (100 Sheets)

The values shown above were developed from random samples taken from production material. We believe them to be typical for the product. However actual values may vary somewhat from those depicted here and R&R Lotion makes no warranty, expressed or implied, as to the suitability of these materials for any specific use. Customers should determine product suitability based upon their own internal criteria. 13 April, 2006



R & R Lotion
15547 N. 77th St
Scottsdale, AZ 85260
480-443-9255